



Dryzone

Revision: 20/08/2007

SAFETY DATA SHEET

1 Identification of the substance or preparation and of the company/undertaking

Product Name: **Dryzone**

Datasheet Number: DZ 2. 0. 0

Product Use: Masonry Damp Proof Course Cream

Name of Supplier: Safeguard Europe Ltd.

Address of Supplier: Redkilm Close

Redkilm Way

Horsham

W.Sussex RH13 5QL

Telephone: 01403 210204

Fax: 01403 217529

Responsible Person:

Email:

Emergency Telephone:

2 Composition/information on ingredients

Chemical Name Concentration CAS Number EC Number R Phrases* Symbols

Triethoxy(2,4,4-trimethyl

pentyl)silane

30-60% 35435-21-3 252-558-1 R10-52/53 None

Bentonite 1-5% 14808-60-7 None None None

Triethoxyoctylsilane 10-30% 2943-75-1 220-941-2 R38 Xi

*See Section 16

3 Hazards identification

- Odour: Faint characteristic odour
- Appearance: cream, white
- Contact with eyes: May cause irritation
- Contact with skin: May cause irritation
- Inhalation: Not expected to present a hazard
- Ingestion: May cause gastro-intestinal disturbances

4 First aid measures

Contact with skin

- Remove contaminated clothing
- Wash affected area with plenty of soap and water
- When in doubt or symptoms persist, seek medical attention

Contact with eyes

- If substance has got into eyes, immediately wash out with plenty of water for at least 15 minutes
- Irrigate eyes thoroughly whilst lifting eyelids
- Seek medical attention if irritation persists

Ingestion

- Do not induce vomiting
- Rinse mouth with water (do not swallow)
- Give 200-300mls (half pint) water to drink
- Seek medical attention

Inhalation

- If high concentrations are inhaled, and any irritation is experienced, remove to fresh air
- When in doubt or symptoms persist, seek medical attention

5 Fire-fighting measures

- Combustible, Flash point 74 deg C (CC)
- Carbon oxides may be formed
- Substance evolves toxic fumes, wear self-contained breathing apparatus
- In case of fire use water, foam, carbon dioxide or dry agent (S43)

6 Accidental release measures

Personal Precautions

- Shut off all ignition sources
- Wash thoroughly after dealing with spillage

Environmental Precautions

- Use appropriate containment to avoid environmental contamination (S57)
- Do not allow to enter public sewers and watercourses

Clean Up Actions

- Absorb spillage in inert material and shovel up
- Place in appropriate container

7 Handling and storage

Handling

- Wash hands thoroughly after using this substance
- When using do not eat, drink or smoke (S20/21)
- Avoid contact with acid
- Avoid contact with oxidising substances
- Keep away from heat and sources of ignition
- Avoid contact with skin (S24)

Storage

- Keep in a cool, dry, well ventilated place
- Store above 5 °C
- Keep container tightly closed (S7)

8 Exposure controls and personal protection

Exposure Limits

- There are no recommended or established controls for this product

Bentonite

- MEL / LTEL # ppm 0.3 mg/m³
- (Germany) MAK # ppm 0.15 mg/m³

Exposure controls

- No special ventilation is required unless the product is used in a spray form

Occupational exposure controls

- Respiratory protection may be required under exceptional circumstances when excessive air contamination exists
- Wear goggles giving complete eye protection
- Wear PVC gloves
- Wear apron or other light protective clothing

9 Physical and chemical properties

- Odour: Faint characteristic odour
- Appearance: cream, white
- pH 8
- Completely soluble in water
- Combustible, Flash point 74 deg C (CC)

10 Stability and reactivity

- Stable
- Avoid overheating
- Incompatible with acid, Incompatible with oxidizing substances
- Decomposition products may include oxides of carbon, and silica

11 Toxicological information

Toxicological information

- LC50 (inhalation, rat) >5.2 mg/l/4h

Inhalation

- May cause drowsiness

Contact with skin

- May cause irritation

Contact with eyes

- May cause irritation

Ingestion

- May cause gastro-intestinal disturbances

12 Ecological information

Ecotoxicity

- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R52/53)

Mobility

- No information available

Persistence and Biodegradability

- Not readily biodegradable

Bioaccumulation Potential

- No information available

13 Disposal considerations

Classification

- This material and/or its container must be disposed of as hazardous waste

Disposal considerations

- In UK, surplus product should be declared a 'Special Waste'. Refer to the 'Control of Pollution (Special Waste) Regulations 1980 - SI 1709'

- Disposal should be in accordance with local, state or national legislation

14 Transport information

- Not classified as hazardous for transport

15 Regulatory information

Classification and labelling

- This Safety Data Sheet does not constitute a workplace risk assessment

Applicable Laws

- This Safety Data Sheet is provided in compliance with The Safety Data Sheets Directive (2001/58EC)

Risk Phrases

- Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment (R52/53)

Safety Phrases

- Avoid release to the environment. Refer to special instructions/Safety data sheets (S61)

16 Other information

Text of R and S phrase codes used in this safety data sheet:- R10: Flammable; R38: Irritating to skin; R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.