

SAFEGUARD



Chemicals S.A.

Manufacturers & Distributors of Waterproofing & Dampproofing Products. Reg No
2005/149627/23

TORCH-ON MEMBRANE

**4mm polymer elastoplastomeric bitumen membrane re-inforced
by non-woven polyester continuous strand**

1. USES

- Flat Roofs
- Slab covering
- Plant Boxes

2. ADVANTAGES

- Excellent weathering properties.
- Tough and flexible.
- Excellent adhesion.
- Ease of application.

3. LIMITATIONS

Do not apply if rain is imminent.

4. COVERAGE

Each roll covers 10m².

5. SURFACE PREPARATION.

All surfaces should be sound, clean and free from any contaminants.

6. APPLICATION

Surfaces must first be treated with a suitable Bitumen Primer.

Torch-on application of the membrane should always be done in temperatures above 5°C.

Care should be taken not to overheat the membrane as this will cause damage to the re-inforcement.

There should be transverse overlapping of the rolls by about 10cm and longitudinal overlapping by about 15cm.

The finished surface should be coated in a suitable UV protective layer which should be renewed every 2-3 years depending upon local conditions.

7. DISPOSAL

Dispose in accordance with local regulations.

8. HEALTH & SAFETY

Safety data sheets available on request.

Safeguard Chemicals SA (Pty) Ltd. PO Box 1032, Sundowner 2161

Tel: +27 11 708 3603 Fax: +27 11 708 3620. E-mail: info@safeguardchem.co.za

All products should be used in accordance with the manufacturer's instructions. Whilst any information and/or specification contained herein, is to the best of our knowledge, true and accurate, no warranty is given, or implied in connection with any recommendations, or suggestions made by us, our representatives, agents or distributors as every possible variation in the method of its use or conditions under which it is applied cannot be anticipated.