



ACRYLSEAL

A liquid-applied waterproofing acrylic, reinforced with acrylic membrane to provide a seamless waterproofing system.

1. USES

- All types of Flashings.
- Parapet Walls.
- Flat roofs smaller than 500m².
- Re-waterproofing over existing waterproofing systems.
- Sealing joints, laps and roofing screws on corrugated roofs.

2. ADVANTAGES

- Excellent weathering properties.
- Tough and flexible.
- Excellent adhesion.

3. LIMITATIONS

Do not apply **Acrylseal** if rain is imminent.

4. COVERAGE

2.5 square metres per litre with membrane.

5. SURFACE PREPERATION.

All surfaces should be sound, clean and free from any contaminants including rust.

6. APPLICATION

Priming

All surfaces except iron and steel, should be primed using **Acryl Prime**.
Iron and steel should be primed using a suitable corrosion resistant etch primer.

First Coat

Apply a generous coat of **Acrylseal** by brush or roller (1 litre/m²)
Bed the membrane into the wet coat, taking care to remove all air pockets and crease marks.
Overlaps must be a minimum of 50mm.

Second Coat

Immediately apply a second coat to fully saturate the membrane from top and bottom.

Final Coat

Once the second coat is touch dry apply final topcoat.

SAFEGUARD



MANUFACTURERS & DISTRIBUTORS OF WATERPROOFING & DAMP PROOFING PRODUCTS.

Chemicals S.A.

Reg No 2005/149627/23

SAFEGUARD CHEMICALS

MANUFACTURERS & DISTRIBUTORS

WATERPROOFING & DAMP PROOFING PRODUCTS

7. CLEANING

Uncured Acrylseal can be removed with water
Cured material can only be removed mechanically.

8. DISPOSAL

Dispose in accordance with local regulations.

9. HEALTH AND SAFETY

Safety data sheets –available on request

Shelf life	12 Month in unopened container.
Storage	Store under cover, and protect from frost.
Colour	Different colours are available.
Drying time	2-3 hours depending on conditions.
Cleaning	Uncured- water. Cured-Mechanical.
Coverage	2.5litre per square metre for full system.
Packaging	20litre, 5litre

Safeguard Chemicals SA. PO Box 1032, Sundowner 2161

Tel: +27 11 708 3603 Fax: +27 11 708 3620. E-mail: info@safeguardchem.co.za

All products should be used in accordance with the manufacturer's instructions. Whilst any information and/or specification contained herein, is to the best of our knowledge, true and accurate, no warranty is given, or implied in connection with any recommendations, or suggestions made by us, our representatives, agents or distributors as every possible variation in the method of its use or conditions under which it is applied cannot be anticipated.