

SAFEGUARD**MANUFACTURERS & DISTRIBUTORS OF WATERPROOFING & DAMP PROOFING PRODUCTS.**

Chemicals S.A.

Reg No 2005/149627/23

BITUMEN ALUMINIUM PAINT

Solvent-based bitumen, pigmented with Aluminium flakes

1. USES

Reflective top coat for all bituminous products.

2. ADVANTAGES

UV resistant.

3. LIMITATIONS

- Do not apply if rain is expected.
- Not to be applied on damp surfaces.
- Must be stirred before and during application.

4. COVERAGE

7 square meter per litre.

5. MIXING

Mix well before use, using a flat paddle. To prevent settlement keep stirring during use.

6. SURFACE PREPERATION.

All surfaces should be sound, clean and **DRY**.

7. APPLICATION

- Apply by using brush roller or spray.
- A two-coat system is advisable.

8. CLEANING

Cured and uncured Bitumen Aluminium can be removed with Solvent Tool Cleaner.

9. DISPOSAL

Dispose in accordance with local regulations.

SAFEGUARD



MANUFACTURERS & DISTRIBUTORS OF WATERPROOFING & DAMP PROOFING PRODUCTS.

Chemicals S.A.

Reg No 2005/149627/23

10. HEALTH & SAFETY

- Solvent based, allow for adequate ventilation
- Flammable, contact with naked flames should be avoided.

Shelf life	12 Month in unopened container.
Storage	Store under cover in dry conditions.
Colour	Silver
Drying time	1-2 hours depending on conditions.
Cleaning	Solvent tool cleaner.
Coverage	7 square meter per liter per coat.
No of coats	2
Packaging	25litre

Safeguard Chemicals SA. PO Box 1032, Sundowner 2161

Tel: +27 11 708 3603 Fax: +27 11 708 3620. E-mail: info@safeguardchem.co.za

All products should be used in accordance with the manufacturer's instructions. Whilst any information and/or specification contained herein, is to the best of our knowledge, true and accurate, no warranty is given, or implied in connection with any recommendations, or suggestions made by us, our representatives, agents or distributors as every possible variation in the method of its use or conditions under which it is applied cannot be anticipated.