


SAFEGUARD**MANUFACTURERS & DISTRIBUTORS OF WATERPROOFING & DAMP PROOFING PRODUCTS.****Chemicals S.A.**

Reg No 2005/149627/23

Mini 2000 Moisture Meter



The definitive general purpose moisture meter

The most widely used moisture meters in the world are probably the Mini series. These compact, general purpose moisture meters are used by building professionals and trades across the globe to check the moisture level of wood and masonry products for a vast range of quality control and dampness diagnosis applications.

Features

The new version of the famous Mini moisture meter has now been launched. The new Mini incorporates a range of design refinements and features that make it much simpler to use than the instrument it supercedes. The stylish instrument case fits snugly in the hand, so it can be used effortlessly for long periods and the new display is very bright for visual clarity.

Also if the instrument is inadvertently left on, it switches off automatically after five minutes to conserve the battery life.

The instrument combines sympathetic design with optimised functionality.

With 20 red Light Emitting Diodes to indicate moisture : Green (dry), Orange (investigate), Red (unsafe) – for checking Wood, Plaster & Screeds etc.

Can also be used as a salts detector

Specifications

Range : 6 – 90 Moisture Level Weight : 250 g (packed)

Resolution : 1% for 6-25% Battery : One 9v

10% up to 100% WME Size : 18 x 4.5 x 3 cm

Warranty : 1 Year

SAFEGUARD



MANUFACTURERS & DISTRIBUTORS OF WATERPROOFING & DAMP PROOFING PRODUCTS.

Chemicals S.A.

Reg No 2005/149627/23

SAFEGUARD CHEMICALS

MANUFACTURERS & DISTRIBUTORS

WATERPROOFING & DAMP PROOFING PRODUCTS

Wood Moisture Equivalent (WME)

The Mini 2000 moisture meters are calibrated for wood but are also suitable for measuring moisture levels in other materials. They are highly versatile tools for assessing the moisture condition of a wide range of non-conductive materials.

In wood, the instruments measure the material's actual percent moisture content (%H₂O).

When testing material other

than wood, the meters measure the wood moisture equivalent (WME) value of the material.

WME is the moisture level

that would be attained by a piece of wood in equilibrium with the material being tested. As the critical moisture levels for

wood are known, WME measurements enable the moisture meter user to establish if

materials are in a safe air dry,

borderline or damp condition.

Shipping List

Supplied with Pouch, Moisture Remote Probe, Calchecker and Wood Calibration table (%MC)

Optional Accessories both (1) & (2) plug into jack plug – (adjacent to needles)

(1) **Deep Wall Probes (5018 & 5020)** (with insulated stems & bare tips) can detect moisture levels up to 140 &

240 mm Length depth. Supplied in a Canvas (Velcro) Pouch.

(2) **Hammer Electrode (5000)** which penetrates to 37 mm into hard wood is supplied with Extra Heavy Duty

needles which have insulated stems & bare tips (in Pouch).

Note : Hammer Electrode readings are more meaningful and less destructive than an Oven Drying Test. The oven gives an **Average** moisture content. The Hammer Electrode enables the user to measure the **High** moisture content.

Safeguard Chemicals SA. PO Box 1032, Sundowner 2161

Tel: +27 11 708 3603 Fax: +27 11 708 3620. E-mail: info@safeguardchem.co.za

All products should be used in accordance with the manufacturer's instructions. Whilst any information and/or specification contained herein, is to the best of our knowledge, true and accurate, no warranty is given, or implied in connection with any

recommendations, or suggestions made by us, our representatives, agents or distributors as every possible variation in the method of its use or conditions under which it is applied cannot be anticipated.