

Certificate of Test

Title:

SAFEGUARD CHEMICALS LTD

Water Permeability Determination

SWS Grey + Bondaid Coated Concrete

Certificate of Test No: **6477**

Client's Name & Address:

**Safeguard Chemicals Ltd
Redkiln Close
Redkiln Way
Horsham
Sussex, RH13 5QL**

Our Ref: **N956/AML/JM/177**
TEL Job No: **6CB5**
Your Ref: **-**
Date: **5th December, 2001**
Date Sample(s) Received: **22nd October, 2001**
Sample(s) Received From: **Mr D White**

Sample No(s): **129137 and 129373**

Tested By: *AMcL* **A McLintock**

Authorised By: *ATB* **A T Blake**

Job Title: **Manager, Analytical Laboratories**
for

TAYWOOD ENGINEERING
CONSULTANTS IN DESIGN AND TECHNOLOGY

Technology
345 Ruislip Road, Southall, Middlesex, UB1 2QX
Tel. No. 020 8578 2388 Fax No. 020 8575 4215
Registered Office Southall Registered No. 1090801 England

This Certificate of Test is copyright. Reproduction of the whole or any part thereof must not be made without the express permission of Taywood Engineering.

This Certificate and the results shown are based upon the information drawings samples and tests referred to herein.

Taywood Engineering accepts no liability for any damages, charges costs (including, but not limited to, legal costs) or expenses in respect of or in relation to any damage to any property or other loss (save for death or personal injury occasioned by reason of any negligence on the part of Taywood Engineering) whatsoever arising directly or indirectly from the use of any goods or materials referred to in this Certificate of Test.

TEL

1. SAMPLE DETAILS

Two 100mm diameter concrete disc samples, one coated, one uncoated, were received by the Analytical Laboratories. The concrete disc substrates were supplied by Taywood Engineering to Safeguard Chemicals Ltd, who applied SWS grey + Bondaid coating material to one substrate only.

The samples were conditioned in laboratory ambient conditions for 28 days before testing.

The uncoated substrate was to be tested for control purposes only.

Taywood Engineering were requested to determine the negative resistance to water permeability of the samples with increasing pressure until failure, i.e. passage of water through the concrete to the coating.

2. METHOD

2.1 Sample Preparation

The sides of the samples were sealed with epoxy resin, by placing in a circular mould and filling the annular space with a cold curing epoxy resin. When the resin had cured, the specimens were demoulded and their water permeability determined.

2.2 Water Permeability Determination

The procedure followed was to apply water, increasing in pressure at a rate of 1 bar per day up to 10 bar or failure. This pressurised water was applied to the underside (uncoated surface) of the sample.

A diagram of the test equipment is shown in Figure 1. The testing was undertaken in the laboratory at $23 \pm 2^\circ\text{C}$ and ambient Relative Humidity.

3. RESULTS


Table 1

DATE	TIME	PRESSURE (BAR)	129137 CONTROL	129373 SWS GREY + BONDAID
21.11.01	11.00	1	Start	Start
22.11.01	08.00	1	Water on surface	-
22.11.01	11.00	2		-
23.11.01	11.00	3		-
26.11.01	08.45	3		Surface damp at edge
26.11.01	11.00	4		No change
27.11.01	09.00	4		Water on surface
27.11.01	11.00	5		No change

Remarks: The coating, SWS grey + Bondaid, failed at 4 bar pressure, equivalent to 40 metre head of water.

WATER PERMEABILITY TEST

FIGURE 1



END OF CERTIFICATE